

TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: NYLON 46
 FLAMABILITY RATING: UL94-V0
 COLOR: BEIGE
 CONTACT MATERIAL: COPPER ALLOY
 CONTACT TYPE: STAMPED
 CONTACT PLATING: TIN
 QUALITY CLASS: 25 MATING CYCLES
 PITCH: 1.25MM

ENVIRONMENTAL
 OPERATING TEMPERATURE: -25 UP TO 85°C
 COMPLIANCE: LEAD FREE AND ROHS


ELECTRICAL
 CURRENT RATING: 1A
 WORKING VOLTAGE: 125V AC
 INSULATOR RESISTANCE: >100 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 250V AC/MN
 CONTACT RESISTANCE: 20 mOHM MAX

STANDARD
 CERTIFIED: E323964

SOLDERING
 SOLDER TEMP.: JEDEC LEAD FREE REFLOW SOLDERING

PACKAGING
 TAPE AND REEL

DIMENSION
 A = 1.25 x (NB PIN - 1)
 B = 1.25 x (NB PIN + 1) + 3.5
 C = 1.25 x (NB PIN + 1) + 0.5

RoHS Compliant							
G	07-AUG-13	CHARACTERISTIC	QL	PROJECTION: 	GENERAL TOLERANCE .X = +/_ 0.2 .XX = +/_ 0.15	 WÜRTH ELEKTRONIK	
F	21-MAR-13	COPLANARITY	AR				
E	29-OCT-12	PIN	GG				
D	22-JUN-12	P&P ZONE	GG				
C	17-NOV-09	STANDARD	JP	APPROVAL: RJ	UNIT: MM	DESCRIPTION: 1.25 MM SMT MALE VERTICAL SHROUDED HEADER	SIZE A4
B	25-MAY-09	PACKAGING	JC		SCALE:		
A	23-JUN-08	PDF	CH		SHEET: 1/2	WERI PART NO: 6531xx124022	
REV	DATE	FILE	BY		DRAW: CEL KING		

