

Gamme budget

Fig.	AWG	Épaisseur de base (en pouces)	Matériau et finition	Fits Tab Size (Inch)∅	Isol. Diam. (en pouces)	N° de référence Digi-Key	Prix de bande coupée			N° de référence Digi-Key	Bande et bobine		N° de référence AMP
							100	500	1 000		Qté	Prix	
Série 0,250" - Support d'isolation													
1	20-14	.012	Laiton	.250 x .032	.085 - .135	A29936CT-ND	9.60	44.04	80.06	A29936TR-ND	12,000	43.24/M	63648-1
	18-22	.016	Laiton	.250 x .032	.090 - .130	A27608CT-ND	6.65	27.70	44.33	A27608TR-ND	10,000	29.92/M	42510-1
	18-22	.016	Laiton étamé	.250 x .032	.090 - .130	A27609CT-ND	7.61	31.72	50.75	A27609TR-ND	10,000	34.26/M	42510-2
	14-18	.016	Laiton	.250 x .032	.120 - .170	A27610CT-ND	5.26	21.91	35.06	A27610TR-ND	10,000	23.67/M	42400-1
	14-18	.016	Laiton étamé	.250 x .032	.120 - .170	A27611CT-ND	5.88	24.49	39.19	A27611TR-ND	10,000	26.46/M	42400-2
Repérage													
2	12-18	.016	Laiton	.250 x .032	.110 - .210	A27612CT-ND	7.28	30.35	48.57	A27612TR-ND	4,000	36.43/M	42511-1
	12-18	.016	Laiton étamé	.250 x .032	.110 - .210	A27613CT-ND	7.53	31.40	50.24	A27613TR-ND	4,000	37.68/M	42511-2
3	18-22	.016	Laiton	.250 x .032	.060 - 1.00	A27618CT-ND†	8.76	36.50	58.39	A27618TR-ND†	9,000	43.80/M	62718-1
	18-22	.016	Laiton étamé	.250 x .032	.060 - 1.00	A27619CT-ND†	13.79	57.44	91.90	A27619TR-ND†	11,000	68.93/M	62718-2
	14-18	.016	Laiton	.250 x .032	.110 - .160	A27614CT-ND▲	11.96	49.83	79.74	A27614TR-ND▲	11,000	59.81/M	63009-1
	14-18	.016	Laiton étamé	.250 x .032	.110 - .160	A27615CT-ND▲	7.02	29.23	46.77	A27615TR-ND▲	10,000	35.08/M	63009-2
	14-18	.016	Laiton	.250 x .032	.110 - .160	A27616CT-ND†	6.66	27.74	44.37	A27616TR-ND†	9,000	33.29/M	63010-1
4	14-18	.016	Laiton étamé	.250 x .032	.110 - .160	A27617CT-ND†	8.11	33.79	54.06	—	—	—	63010-2
Force d'insertion nulle													
4	22-18	.016	Laiton/Étain	.250 x .032	.090 - .130	A29940CT-ND	10.38	47.59	86.52	A29940TR-ND	10,000	46.73/M	63609-2
	18-14	.016	Acier/Nickel	.250 x .032	.120 - .170	A29941CT-ND	10.45	47.88	87.07	A29941TR-ND	10,000	47.02/M	63674-1
	14-18	.016	Laiton	.250 x .032	.120 - .170	A27780CT-ND	6.01	25.01	40.02	A27780TR-ND	10,000	27.02/M	63306-1
	14-18	.016	Laiton étamé	.250 x .032	.120 - .170	A27781CT-ND	6.69	27.89	44.61	A27781TR-ND	10,000	30.12/M	63306-2
	14-10	.018	Laiton étamé	.250 x .032	.225 - .275	A29942CT-ND	10.03	45.96	83.58	A29942TR-ND	6,000	50.15/M	63539-1
4	10-14	.018	Laiton étamé	.250 x .032	.150 - .200	A27783CT-ND	10.01	41.71	66.73	A27783TR-ND	9,000	50.05/M	63365-2
Série 0,187" - Support isolant													
1	16-20	.012	Laiton	.187 x .020	.090 - .130	A27715CT-ND	4.13	17.18	27.49	A27715TR-ND	20,000	18.56/M	42617-1
	16-20	.012	Laiton étamé	.187 x .020	.090 - .130	A27716CT-ND	4.41	18.38	29.41	A27716TR-ND	20,000	19.85/M	42617-2
	16-20	.012	Laiton	.187 x .032	.090 - .130	A27717CT-ND	7.27	30.30	48.47	A27717TR-ND	20,000	32.72/M	61919-1
Repérage													
2	16-20	.012	Laiton	.187 x .020	.110 - .170	A27718CT-ND	5.85	24.40	39.03	A27718TR-ND	6,000	29.27/M	42618-1
	16-20	.012	Laiton étamé	.187 x .020	.110 - .170	A27719CT-ND	6.46	26.92	43.07	A27719TR-ND	6,000	32.31/M	42618-2
Force d'insertion nulle													
4	16-20	.012	Laiton	.187 x .020	.090 - .130	A27786CT-ND	6.36	26.50	42.40	A27786TR-ND	20,000	28.62/M	63475-1
	16-20	.012	Laiton étamé	.187 x .020	.090 - .130	A27787CT-ND	4.82	20.08	32.12	A27787TR-ND	20,000	21.69/M	63475-2
	16-20	.012	Laiton	.187 x .032	.090 - .130	A27788CT-ND	6.82	28.41	45.45	A27788TR-ND	20,000	30.68/M	63477-1
	16-20	.012	Laiton étamé	.187 x .032	.090 - .130	A27789CT-ND	7.65	31.90	51.04	A27789TR-ND	20,000	34.46/M	63477-2

† Repérage à droite ▲ Repérage à gauche ∅ S'ajuste à la taille de la languette (en pouces)

Gamme économique

Fig.	AWG	Épaisseur de base (en pouces)	Matériau et finition	Fits Tab Size (Inch)∅	Isol. Diam. (en pouces)	N° de référence Digi-Key	Prix de bande coupée			N° de référence Digi-Key	Bande et bobine		N° de référence AMP
							100	500	1 000		Qté	Prix	
Série 0,250"													
Support isolant													
1	22-26	.016	Laiton	.250 x .032	.040 - .060	A27620CT-NDΔ	10.59	44.12	70.58	A27620TR-NDΔ	12,000	47.65/M	61202-1
	18-22	.016	Laiton	.250 x .032	.090 - .130	A27621CT-ND	5.13	21.37	34.19	A27621TR-ND	12,000	23.08/M	42743-1
	18-22	.016	Laiton étamé	.250 x .032	.090 - .130	A27622CT-ND	5.77	24.02	38.43	A27622TR-ND	12,000	25.95/M	42743-2
	14-18	.016	Laiton	.250 x .032	.120 - .170	A27623CT-ND	5.13	21.37	34.19	A27623TR-ND	12,000	23.08/M	42660-1
	14-18	.016	Laiton étamé	.250 x .032	.120 - .170	A27624CT-ND	5.77	24.02	38.43	A27624TR-ND	12,000	25.95/M	42660-2
	14-18	.016	Laiton	.250 x .032	.150 - .210	A27625CT-ND	6.60	27.50	44.00	A27625TR-ND	10,000	29.71/M	42692-1
2	14-18	.016	Laiton étamé	.250 x .032	.150 - .210	A27626CT-ND	5.77	24.02	38.43	A27626TR-ND	10,000	25.95/M	42692-2
	18-22	.015	Laiton	.250 x .032	.060 - .100	A27627CT-ND	12.78	53.25	85.20	A27627TR-ND	2,500	74.55/M	61988-1
	18-22	.015	Laiton étamé	.250 x .032	.060 - .100	A27628CT-ND	14.65	61.06	97.69	A27628TR-ND	2,500	85.48/M	61988-2
	14-18	.015	Laiton	.250 x .032	.120 - .170	A27629CT-ND	13.10	54.56	87.29	A27629TR-ND	2,500	76.38/M	61944-1
	14-18	.015	Laiton étamé	.250 x .032	.120 - .170	A27630CT-ND	13.99	58.28	93.24	A27630TR-ND	2,500	81.59/M	61944-2
	14-18	.032-.016	Laiton	.250 x .032	.120 - .170	A27631CT-ND‡	19.77	82.36	131.77	A27631TR-ND‡	2,500	115.30/M	62109-1
14-18	.032-.016	Laiton étamé	.250 x .032	.120 - .170	A27632CT-ND‡	21.25	88.53	141.65	A27632TR-ND‡	2,500	123.95/M	62109-2	
Support non isolant													
3	14-18	.016	Laiton	.250 x .032	—	A27638CT-ND	6.93	28.87	46.19	A27638TR-ND	14,000	31.18/M	42845-1
	14-18	.016	Laiton étamé	.250 x .032	—	A27639CT-ND	6.84	28.51	45.61	A27639TR-ND	14,000	30.79/M	42845-2
4	14-18	.015	Laiton pré-étamé	.250 x .032	—	A27640CT-ND	13.23	55.13	88.22	A27640TR-ND	2,500	77.20/M	62276-1
	10-14	.015	Laiton pré-étamé	.250 x .032	—	A27641CT-ND	28.99	120.80	193.27	A27641TR-ND	2,500	169.11/M	62068-1
Support isolant de repérage													
5	14-18	.016	Laiton	.250 x .032	.110 - .160	A27635CT-ND▲	6.07	25.29	40.47	A27635TR-ND▲	11,000	30.36/M	63096-1
6	12-18	.016	Laiton	.250 x .032	.110 - .210	A27636CT-ND	7.05	29.37	46.99	A27636TR-ND	4,000	35.25/M	42742-1
	12-18	.016	Laiton étamé	.250 x .032	.110 - .210	A27637CT-ND	7.14	29.74	47.57	A27637TR-ND	4,000	35.68/M	42742-2
Support non isolant de repérage													
7	12-18	.016	Laiton pré-étamé	.250 x .032	—	A27642CT-ND†	6.75	28.11	44.97	A27642TR-ND†	5,000	33.73/M	61177-2
	12-18	.016	Laiton pré-étamé	.250 x .032	—	A27643CT-ND§	11.37	47.38	75.80	A27643TR-ND§	4,000	56.86/M	62091-2
	10-12 ou (2)14	.016	Laiton	.250 x .032	—	A27644CT-ND§	10.09	42.04	67.26	A27644TR-ND§	4,000	50.45/M	62011-1
	(2)14	.016	Laiton étamé	.250 x .032	—	A27645CT-ND§	11.44	47.68	76.29	A27645TR-ND§	4,000	57.22/M	62011-2
Série 0,205" - Support d'isolation													
8	18-22	.012	Laiton	.205 x .020	.085 - .125	A27689CT-ND	6.66	27.74	44.37	A27689TR-ND	15,000	29.96/M	42710-1
	18-22	.012	Laiton étamé	.205 x .020	.085 - .125	A27690CT-ND	6.52	27.17	43.46	A27690TR-ND	15,000	29.34/M	42710-2
	18-22	.012	Laiton étamé	.205 x .032	.085 - .125	A27691CT-ND	8.02	33.44	53.50	A27691TR-ND	20,000	36.11/M	60904-2
	14-18	.012	Laiton étamé	.205 x .020	.130 - .180	A27692CT-ND	8.52	35.52	56.82	A27692TR-ND	16,000	38.36/M	42713-2
Série 0,187"													
Support isolant													
1	16-20	.012	Laiton	.187 x .020	.090 - .130	A27720CT-ND	3.99	16.62	26.60	A27720TR-ND	20,000	17.96/M	42801-1
	16-20	.012	Laiton étamé	.187 x .020	.090 - .130	A27721CT-ND	4.46	18.56	29.69	A27721TR-ND	20,000	20.05/M	42801-2
	16-20	.012	Laiton	.187 x .032	.090 - .130	A27722CT-ND	4.80	19.99	31.99	A27722TR-ND	20,000	21.60/M	60196-1
	16-20	.012	Laiton étamé	.187 x .032	.090 - .130	A27723CT-ND	5.15	21.46	34.34	A27723TR-ND	20,000	23.18/M	60196-2
Support non isolant													
3	16-20	.012	Laiton	.187 x .020	—	A27724CT-ND	5.34	22.24	35.57	A27724TR-ND	25,000	22.24/M	42799-1
	16-20	.012	Laiton étamé	.187 x .020	—	A27725CT-ND	7.17	29.86	47.78	A27725TR-ND	25,000	29.87/M	42799-2
Support isolant de repérage													
6	16-20	.012	Laiton	.187 x .020	.110 - .170	A27726CT-ND	4.47	18.64	29.82	A27726TR-ND	6,000	22.37/M	42800-1
	16-20	.012	Laiton étamé	.187 x .020	.110 - .170	A27727CT-ND	5.06	21.08	33.73	A27727TR-ND	6,000	25.30/M	42800-2
	16-20	.012	Laiton	.187 x .032	.110 - .170	A27728CT-ND	6.19	25.78	41.26	A27728TR-ND	6,000	30.95/M	60529-1
	16-20	.012	Laiton étamé	.187 x .032	.110 - .170	A27729CT-ND	5.34	22.24	35.59	A27729TR-ND	6,000	26.70/M	60529-2